



2035 Series High Pressure Filter Assemblies

Features

- High collapse 4500 psid (310 bard) filter element using Rigimesh® stainless steel medium
- Flows to 38 lpm (10 gpm)
- Port sizes: 3/8" NPT, 1/2" NPT

Notes and Specifications

Maximum working pressure:

6,000 psi (413 bar)

Typical burst pressure:

min. 24,000 psi (1655 bar)

Temperature rating:

-10°F (-23°C) to 225°F (107°C)

Materials of Construction:

Head and Body: Stainless Steel

Seal material: PTFE encapsulated fluorocarbon
(Nitrile and Chloroprene also available)

Filter element

collapse pressure: 4500 psid (310 bard)

Element

construction: Rigimesh all stainless steel (no resin binders) medium, stainless steel end caps

Seal Material: Chloroprene, Nitrile, PTFE encapsulated fluorocarbon




Pressure Drop Information

Housing Pressure Drop

Fluid at 14.3 cSt (75 SUS), 0.88 S.G.


Housing pressure drop is directly proportional to specific gravity.




Element Pressure Drop

Fluid at 14.3 cSt (75 SUS), 0.88 S.G.

Correct for other fluids by multiplying new viscosity in cSt/14.3 (SUS/75) x new S.G./0.88.



Dimensional Drawings



Part Numbers/Ordering Information

H ♦ 2035 ▼ ■ ● ✕ ❖ ■ (e.g., HZ2035B06NKRWE1)

Code ♦	Seal Material
H	Nitrile
P	Chloroprene
Z	PTFE encapsulated fluorocarbon

Code ▼	Type of Port
B06	3/8" NPT
B08	1/2" NPT

Code ■	Filter Media Grade Options
NK	5 µm
NJ	10 µm
++	Housing only

Code ●	Length (nominal)
R	4"

Code ✕	Bypass Valve Type
W	Non-bypass, (100 psid indicator setting where equipped)

Code ❖	ΔP Device Options
E	visual, 6,000 psi rated
0	No port
BH	Plug

Code ■	Additional Options
Omit	None
1	Mounting bracket assembly

Rigimesh Element Part Number

HC2035E ■ 4 ♦ Y923 (e.g., HC2035ENK4ZY923)

Code ■	Filter Media Grade Options
NK	5 µm ⁽³⁾
NJ	10 µm ⁽³⁾

Code ♦	Seal Material
H	Nitrile
P	Chloroprene
Z	PTFE encapsulated fluorocarbon

¹ Dimensions are in inches.

² 3.0" required for element removal.

³ 98% efficiency.



USA

25 Harbor Park Drive
Port Washington, NY 11050
+1 888 333 7255 (toll free in U.S. only)
+1 516 484 3600 phone
+1 516 484 6247 fax

United Kingdom

Europa House, Havant Street
Portsmouth PO1 3PD
Hampshire, England
+44 (0) 23 9230 3303 phone
+44 (0) 23 9230 2507 fax
m&e_sales@pall.com email

Visit us on the Web at www.pall.com

Pall Corporation has offices and plants throughout the world in locations including: Argentina, Australia, Austria, Belgium, Brazil, Canada, China, France, Germany, India, Indonesia, Ireland, Italy, Japan, Korea, Malaysia, Mexico, the Netherlands, New Zealand, Norway, Poland, Puerto Rico, Russia, Singapore, South Africa, Spain, Sweden, Switzerland, Taiwan, Thailand, United Kingdom, United States, and Venezuela. Distributors are located in all major industrial areas of the world.